


EARTHMAX SR 35

| | |
|---------------------|--|
| TIRE SIZE | 750/65 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VOLQUETE ARTICULADO / BULDÓCER / PALA CARGADORA |
| VERSIÓN | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 190 B ; 202 A2 |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-----------------------|
| OD (MM) | 1601 | RIM ALT | 22.00/3.0 ; 25.00/3.0 |
| SLR (MM) | 715 | TRA CODE | E3/L3 |
| RC (MM) | 4802 | STAR RATING | ★★★ |
| RIM REC | 24.00/3.0 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 |
|------------|-------|-------|-------|-------|
| 50 | 9500 | 9750 | 10300 | 10600 |
| 10 | 13200 | 14000 | 14500 | 15000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.