

AGRIMAX FORCE

TIRE SIZE	IF 600/70 R 28
UM	IS STANDARD
MACHINERY	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	164 D



DIMENSIONS IS STANDARD

SW (MM)	603	RIM REC	DW 21 B
OD (MM)	1551	RIM ALT	DW 20 B
SLR (MM)	694	ECE	E4-106R-000795
RC (MM)	4654	SRI	725

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2135	2455	2820	3185	3545	3910	4275	4550
FROM 65 TO 40	2350	2700	3100	3500	3900	4300	4700	5000
30	2440	2805	3220	3640	4055	4470	4885	5200
20	2535	2915	3345	3780	4210	4640	5075	5400
10	2980	3425	3935	4445	4950	5460	5965	6350
*UPTO 10 CYC WITH FRONT LOADER	3290	3780	4340	4900	5460	6020	6580	7000
10 HT	2440	2805	3220	3640	4055	4470	4885	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.