

# SM 55 L5S

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>35/65 - 33</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | VEHICUL PENTRU EXPLOATARE<br>MINIERĂ SUBTERANĂ /<br>AUTOBASCULANTĂ CU PROFIL REDUS<br>(LPDT) |
| <b>VERSION</b>      | ARASHIELD  |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIUNI US STANDARD

|                 |           |                 |     |
|-----------------|-----------|-----------------|-----|
| <b>USA CODE</b> | 94063864  | <b>TRA CODE</b> | L5S |
| <b>OD (IN)</b>  | 82.1      |                 |     |
| <b>RIM REC</b>  | 28.00/3.5 |                 |     |
| <b>PR</b>       | 48        |                 |     |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>105</b> |
| 5                | 64000      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.