


AGRIMAX ELOS

| | |
|---------------------|--|
| | 520/85 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAKTÖR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 167 A8/B |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|-------------------|
| USA CODE | 94075850 | RC (IN) | 240.0 |
| SW (IN) | 20.3 | RIM REC | DW 16 L |
| OD (IN) | 78.3 | RIM ALT | DD 18 L ; DW 18 L |
| SLR (IN) | 36.2 | ECE | E11-106R-0010146 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 14 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 30 | 4700 | 5530 | 6370 | 7100 | 7940 | 8650 | 9500 | 10460 | 11300 | 12010 |
| 25 | 4700 | 5530 | 6370 | 7100 | 7940 | 8650 | 9500 | 10460 | 11300 | 12010 |
| 20 | 5030 | 5920 | 6820 | 7590 | 8500 | 9270 | 10160 | 11200 | 12090 | 12860 |
| 5 LT | 6280 | 7420 | 8540 | 9500 | 10640 | 11600 | 12730 | 14020 | 15140 | 16100 |
| 5 HT | 5030 | 5920 | 6820 | 7590 | 8500 | 9270 | 10160 | 11200 | 12090 | 12860 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.