


# TF 8181

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 5.00 - 16  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTEUR 2WD / TRACTEUR /<br>REMORQUE  |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 76 A8  |



## DIMENSIONS US STANDARD

|                 |          |                |                   |
|-----------------|----------|----------------|-------------------|
| <b>CODE USA</b> | 94027774 | <b>RC (IN)</b> | 79.7              |
| <b>SW (IN)</b>  | 5.5      | <b>RIM REC</b> | 4.00 E            |
| <b>OD (IN)</b>  | 26.8     | <b>RIM ALT</b> | 3.00 D; 4 J; 4½ J |
| <b>SLR (IN)</b> | 12.7     | <b>ECE</b>     | E11-106R-004090   |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>62</b> |
| 25               | 880       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.