

AGRIMAX FORCE

TIRE SIZE	IF 650/85 R 38 CFO
UM	IS STANDARD
MACHINERY	MOISSONNEUSE / TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	179 D

DIMENSIONS IS STANDARD

SW (MM)	663	RIM REC	DW 23 B
OD (MM)	2071	RIM ALT	DW 20 B ; DW 21 B
SLR (MM)	927	ECE	E4-106R-002649
RC (MM)	6106	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3310	3805	4370	4935	5500	6065	6625	7050
FROM 65 TO 40	3640	4185	4805	5425	6045	6665	7285	7750
30	3785	4350	4995	5640	6285	6930	7575	8060
20	3930	4515	5185	5855	6525	7195	7865	8370
10	4620	5310	6100	6885	7675	8460	9250	9840
UPTO 30 CYC	4730	5440	6245	7050	7855	8660	9470	10075
UPTO 15 CYC	5640	6485	7445	8405	9365	10330	11290	12010
UPTO 10 CYC	6185	7110	8165	9220	10275	11330	12380	13175
10 HT	3785	4350	4995	5640	6285	6930	7575	8060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

