

# MP 567

**11.5/80 - 15.3**

|                     |   |
|---------------------|---|
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | UYGULAMALI MAKINE / TELESKOPIK<br>YÜKLEYİCİ / UYGULAMALI MAKINE /<br>TELESKOPIK YÜKLEYİCİ / GENEL<br>KULLANIM ARACI |
| <b>VERSION</b>      | IMPLEMENT   |
| <b>TIRE TYPE</b>    | TL  |
|                     | 130 A8  |
|                     | 143 A8  |



## UNDEFINED IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 292  | <b>RIM REC</b> | 9.0             |
| <b>OD (MM)</b>  | 868  | <b>ECE</b>     | E11-106R-003392 |
| <b>SLR (MM)</b> | 393  | <b>PR</b>      | 18              |
| <b>RC (MM)</b>  | 2578 |                |                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>6.00</b> |
| 40 FR             | 2725        |
| 40 DW             | 1900        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.