


# AGRIMAX SIRIO

<b>TIRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	HIGH SPEED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	171 D ; 168 E



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94044283	<b>RC (IN)</b>	229.9
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	77.1	<b>RIM ALT</b>	DW 25 B
<b>SLR (IN)</b>	34.9	<b>ECE</b>	E4-106R-000818

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5810	6670	7660	8640	9630	10630	11490	12350
40	6380	7330	8410	9490	10580	11660	12610	13560
30	6700	7690	8840	9980	11110	12260	13250	14240
25	6990	8020	9210	10390	11580	12780	13810	14850
15	7560	8690	9960	11250	12540	13820	14950	16070
5	9570	10990	12610	14240	15870	17490	18910	20340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.