

AGRIMAX RT 765

TIRE SIZE	320/70 R 20
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / TRACTEUR / MACHINE À VENDANGER / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	123 A8/B



DIMENSIONS US STANDARD

CODE USA	94021932	RIM REC	W 10
SW (IN)	12.6	RIM ALT	W 9 ; W 11
OD (IN)	38.7	ECE	E4-106R-000644
SLR (IN)	17.5	TRA CODE	R1W
RC (IN)	115.7	TREAD DEPTH (32nd)	40.95

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1610	1850	2130	2390	2670	2940	3190	3420
25	1610	1850	2130	2390	2670	2940	3190	3420
20	1730	1980	2270	2570	2850	3150	3410	3660
5 LT	2160	2480	2840	3220	3580	3950	4270	4590
5 HT	1730	1980	2270	2570	2850	3150	3410	3660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.