


AGRIMAX RT 955

TIRE SIZE	270/95 R 36
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	139 A8/B



DIMENSIUNI IS STANDARD

SW (MM)	275	RIM REC	W 9
OD (MM)	1428	RIM ALT	W 8; W 10
SLR (MM)	665	ECE	E4-106R-000659
RC (MM)	4335	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	950	1240	1510	1655	1750	1920	2090	2260	2430	-
40	950	1240	1510	1655	1750	1920	2090	2260	2430	-
30	1020	1330	1620	1775	1880	2060	2245	2425	2605	-
10	1130	1425	1750	2080	2410	2480	2775	3065	3355	3645

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.