

AGRIMAX RT 765

TIRE SIZE	420/70 R 24
UM	US STANDARD
MACHINERY	PULVERIZADOR / TRACTOR / VENDIMIADORA / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	SPECIAL
TIRE TYPE	TL
LI/SS	134 D



DIMENSIONES US STANDARD

CÓDIGO USA	94063277	RIM ALT	W 12 ; W 14 L
SW (IN)	16.5	ECE	E11-106R-005825
OD (IN)	49.1	TRA CODE	R1W
SLR (IN)	21.8	TREAD DEPTH (32 nd)	54.81
RC (IN)	144.9	TMPH (TM/H)	1
RIM REC	W 13		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
40	2340	2710	3090	3510	3880	4250	4670
30	2460	2850	3250	3690	4090	4480	4920
25	2570	2980	3380	3850	4250	4670	5130
20	2690	3130	3560	4030	4480	4910	5380
5 LT	3140	3650	4140	4710	5210	5710	6270
5 HT	2690	3130	3560	4030	4480	4910	5380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.