

# MP 567

|                           |   |
|---------------------------|---|
| <b>TYRE SIZE</b>          | <b>12.0/75 - 18</b>                                     |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | IMPLEMENT MACHINERY /<br>IMPLEMENTS / UNIVERSAL VEHICLE |
| <b>VERSION</b>            | IMPLEMENT   |
| <b>TYRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 126 A8  |
| <b>LI/SS FREE ROLLING</b> | 139 A8  |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 298  | <b>RIM REC</b> | W 9             |
| <b>OD (MM)</b>  | 915  | <b>RIM ALT</b> | 9; 11           |
| <b>SLR (MM)</b> | 426  | <b>ECE</b>     | E11-106R-006701 |
| <b>RC (MM)</b>  | 2723 | <b>PR</b>      | 12              |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.00</b> |
| <b>40 FR</b>      | 2430        |
| <b>40 DW</b>      | 1700        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.