

# PL 801

<b>TIRE SIZE</b>	<b>7.50 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENTS / ROTOR RAKE / TEDDER / FORKLIFT / HARVESTER / FORKLIFT
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TT



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94007325	<b>RC (IN)</b>	0
<b>SW (IN)</b>	8.7	<b>RIM REC</b>	6.0
<b>OD (IN)</b>	32.0	<b>RIM ALT</b>	6.00 S ; 6.5
<b>SLR (IN)</b>	0	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	135	140
<b>15 LOAD WHEEL</b>	7560	-
<b>15 STEER WHEEL</b>	6395	-
<b>5 OTHER VEHICLES</b>	6395	-
<b>15 OTHER VEHICLES</b>	4695	-
<b>STATIC SIDE LOADER</b>	-	10330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.