


AGRIMAX V-FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 710/60 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MOTORSTARK TRAKTOR / TRAKTOR |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 174 D |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94514182 | RC (IN) | 239.8 |
| SW (IN) | 28.1 | RIM REC | DW 25 B |
| OD (IN) | 80.4 | RIM ALT | DW 27 B |
| SLR (IN) | 35.3 | ECE | E11-106R-0011234 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 14 | 17 | 20 | 23 |
|---------------|-------|-------|-------|-------|-------|-------|
| 45 | 7400 | 8610 | 9820 | 11030 | 12250 | 13450 |
| FROM 40 TO 25 | 8120 | 9460 | 10790 | 12110 | 13450 | 14770 |
| 20 | 8290 | 9640 | 11000 | 12360 | 13710 | 15070 |
| 12 | 8450 | 9840 | 11220 | 12610 | 13990 | 15370 |
| 5 | 8940 | 10410 | 11870 | 13330 | 14790 | 16250 |
| UPTO 20 CYC | 9230 | 10740 | 12250 | 13760 | 15270 | 16770 |
| UPTO 10 CYC | 11010 | 12820 | 14620 | 16420 | 18220 | 20020 |
| UPTO 5CYC | 12070 | 14040 | 16020 | 17990 | 19960 | 21930 |
| 5 HT | 8290 | 9640 | 11000 | 12360 | 13710 | 15070 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.