

# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>540/65 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	152 D ; 155 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	530	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1566	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	712	<b>ECE</b>	E4-106R-000652
<b>RC (MM)</b>	4742	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1705	1990	2240	2485	2735	2950	3270	3550
<b>50</b>	1795	2090	2350	2615	2875	3100	3435	3730
<b>40</b>	1860	2170	2445	2715	2985	3220	3565	3875
<b>30</b>	1965	2290	2575	2860	3150	3395	3760	4085
<b>10 LT</b>	2285	2670	3000	3335	3670	3955	4380	4760
<b>10 HT</b>	1965	2290	2575	2860	3150	3395	3760	4085

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.