

FLOTATION 648

TIRE SIZE	600/50 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	147 A8/144 B
LI/SS FREE ROLLING	159 A8/156 B



ABMESSUNGEN IS STANDARD

SW (MM)	611	RIM REC	AG 20.00
OD (MM)	1170	ECE	E4-106R-002312
SLR (MM)	510	PR	12
RC (MM)	3501		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.70	2.00
10 FR	5175	5570	6125
20 FR	4655	5015	5515
30 FR	4140	4460	4900
40 FR	3695	3980	4375
50 FR	3325	3580	4000
10 DW	3640	3915	4305
20 DW	3275	3520	3875
30 DW	2910	3130	3445
40 DW	2600	2795	3075
50 DW	2340	2515	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.