


# AGRIMAX RT 955

<b>TYRE SIZE</b>	<b>300/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	144 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94040636	<b>RC (IN)</b>	190.9
<b>SW (IN)</b>	11.6	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	62.1	<b>RIM ALT</b>	W 10 ; W 11
<b>SLR (IN)</b>	29.3	<b>ECE</b>	E4-106R-001396

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	2540	3270	3960	4320	4630	5070	5500	5860	6150	-
25	2540	3270	3960	4320	4630	5070	5500	5860	6150	-
20	2710	3510	4230	4630	4960	5420	5890	6280	6610	-
5	2880	3620	4450	5280	6120	6300	7040	7780	8520	9260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.