

# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>620/70 R 42</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL                   |
| <b>MACHINERY</b>    | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 166 D  |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94063505 | <b>RC (IN)</b> | 228.4           |
| <b>SW (IN)</b>  | 24.6     | <b>RIM REC</b> | DW 20 B         |
| <b>OD (IN)</b>  | 76.2     | <b>RIM ALT</b> | DW 18 L         |
| <b>SLR (IN)</b> | 34.5     | <b>ECE</b>     | E11-106R-005998 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17    | 20    | 23    | 29    | 35    |
|-----------|------|------|------|-------|-------|-------|-------|-------|
| 40        | 5500 | 6320 | 7250 | 8180  | 9120  | 10050 | 10990 | 11680 |
| 30        | 5780 | 6640 | 7620 | 8600  | 9580  | 10560 | 11540 | 12270 |
| 25        | 6020 | 6910 | 7940 | 8960  | 9990  | 11010 | 12040 | 12800 |
| 20        | 6320 | 7260 | 8330 | 9410  | 10480 | 11560 | 12630 | 13440 |
| 5 LT      | 7360 | 8470 | 9720 | 10970 | 12220 | 13480 | 14730 | 15660 |
| 5 HT      | 6320 | 7260 | 8330 | 9410  | 10480 | 11560 | 12630 | 13440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.