


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 250/85 R 22 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 113 A8/B |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 251 | RIM REC | W 8 |
| OD (MM) | 985 | RIM ALT | W 7 |
| SLR (MM) | 453 | ECE | E11-106R-002973 |
| RC (MM) | 2964 | SRI | 475 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|-----|-----|-----|------|------|------|------|------|
| 50 | 545 | 625 | 715 | 805 | 900 | 990 | 1070 | 1150 |
| 40 | 545 | 625 | 715 | 805 | 900 | 990 | 1070 | 1150 |
| 30 | 585 | 670 | 770 | 865 | 965 | 1065 | 1150 | 1235 |
| 10 LT | 730 | 835 | 960 | 1085 | 1210 | 1330 | 1440 | 1545 |
| 10 HT | 585 | 670 | 770 | 865 | 965 | 1065 | 1150 | 1235 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.