


# AW 09

<b>TIRE SIZE</b>	<b>300/80 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	129 A8
<b>LI/SS FREE ROLLING</b>	141 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	295	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	860	<b>ECE</b>	E4-106R-000376
<b>SLR (MM)</b>	376		
<b>RC (MM)</b>	2520		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575
10 DW	2590
25 DW	2200
30 DW	2070
40 DW	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.