


# AGRIMAX FORCE

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>IF 710/75 R 34</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR                                   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 178 D  |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94053643 | <b>RC (IN)</b> | 227.4           |
| <b>SW (IN)</b>  | 28.2     | <b>RIM REC</b> | DW 25 B         |
| <b>OD (IN)</b>  | 75.9     | <b>RIM ALT</b> | DW 23 B         |
| <b>SLR (IN)</b> | 34.3     | <b>ECE</b>     | E11-106R-003017 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI            | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45                   | 7070  | 8120  | 9330  | 10530 | 11730 | 12930 | 14140 | 15050 |
| <b>FROM 40 TO 25</b> | 7770  | 8930  | 10250 | 11570 | 12900 | 14220 | 15540 | 16500 |
| 20                   | 8080  | 9280  | 10660 | 12040 | 13400 | 14780 | 16160 | 17200 |
| 12                   | 8390  | 9630  | 11070 | 12500 | 13920 | 15350 | 16780 | 17860 |
| 5                    | 9870  | 11330 | 13020 | 14690 | 16370 | 18050 | 19730 | 21000 |
| <b>UPTO 20 CYC</b>   | 10100 | 11610 | 13330 | 15050 | 16770 | 18480 | 20200 | 21490 |
| <b>UPTO 10 CYC</b>   | 12040 | 13830 | 15880 | 17930 | 19980 | 22030 | 24080 | 25630 |
| <b>UPTO 5 CYC</b>    | 13200 | 15180 | 17430 | 19680 | 21920 | 24170 | 26420 | 28110 |
| 5 HT                 | 8080  | 9280  | 10660 | 12040 | 13400 | 14780 | 16160 | 17200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.