

FLOTATION 648

TIRE SIZE	500/50 - 17
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	145 A8/141 B
LI/SS FREE ROLLING	157 A8/154 B



РАЗМЕРЫ US STANDARD

USA CODE	94040346	RC (IN)	108.3
SW (IN)	20.1	RIM REC	16.00
OD (IN)	37.2	ECE	E4-106R-002305
SLR (IN)	16.4	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	55	57	58
5 FR	12360	12540	12730
10 FR	11120	11290	11460
20 FR	9890	10040	10180
25 FR	8830	8960	9090
30 FR	7950	8070	8270
5 DW	8690	8810	8950
10 DW	7810	7930	8060
20 DW	6960	7050	7160
25 DW	6210	6290	6390
30 DW	5590	5670	5680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.