

# AGRIMAX RT 855

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>250/85 R 22</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                              |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 113 A8/B                                                              |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94049332 | <b>RC (IN)</b> | 116.7           |
| <b>SW (IN)</b>  | 9.9      | <b>RIM REC</b> | W 8             |
| <b>OD (IN)</b>  | 38.8     | <b>RIM ALT</b> | W 7             |
| <b>SLR (IN)</b> | 17.8     | <b>ECE</b>     | E11-106R-002973 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|------|------|------|------|------|------|------|------|
| <b>30</b>   | 1200 | 1380 | 1580 | 1770 | 1980 | 2180 | 2360 | 2540 |
| <b>25</b>   | 1200 | 1380 | 1580 | 1770 | 1980 | 2180 | 2360 | 2540 |
| <b>20</b>   | 1290 | 1480 | 1700 | 1910 | 2130 | 2350 | 2540 | 2720 |
| <b>5 LT</b> | 1610 | 1840 | 2120 | 2390 | 2670 | 2930 | 3170 | 3410 |
| <b>5 HT</b> | 1290 | 1480 | 1700 | 1910 | 2130 | 2350 | 2540 | 2720 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.