


AGRIMAX RT 600

| | |
|---------------------|--|
| TIRE SIZE | 620/75 R 26 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CEIFEIRA / ESPALHADOR / TRATOR / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 167 A8/B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94050444 | RC (IN) | 191.0 |
| SW (IN) | 24.6 | RIM REC | DW 20 B |
| OD (IN) | 62.6 | ECE | E11-106R-002993 |
| SLR (IN) | 28.7 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 20 | 23 | 29 | 35 | 41 | 46 | 49 | 55 |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5530 | 6370 | 7810 | 8530 | 9380 | 10220 | 11060 | 12010 | - | - |
| 25 | 5530 | 6370 | 7810 | 8530 | 9380 | 10220 | 11060 | 12010 | - | - |
| 20 | 5920 | 6820 | 8370 | 9140 | 10040 | 10930 | 11840 | 12860 | - | - |
| 5 LT | 7420 | 8540 | 10470 | 11440 | 12570 | 13690 | 14830 | 16100 | - | - |
| 5 HT | 5920 | 6820 | 8370 | 9140 | 10040 | 10930 | 11840 | 12860 | - | - |
| 5 CYC. | - | 9090 | 11650 | 12780 | 14810 | 16250 | 17780 | 19310 | 19610 | 20420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.