

# AGRIMAX RT 765

|                  |                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>480/70 R 34</b>                                                                                 |
| <b>UM</b>        | US STANDARD                                                                                        |
| <b>MACHINERY</b> | FELDSPRITZE / TRACTOR /<br>TRAUBENERNTEMASCHINE /<br>ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| <b>VERSION</b>   | SPECIAL                                                                                            |
| <b>TIRE TYPE</b> | TL                                                                                                 |
| <b>LI/SS</b>     | 149 D                                                                                              |



## ABMESSUNGEN US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA-CODE</b> | 94062300 | <b>RC (IN)</b> | 187.9           |
| <b>SW (IN)</b>  | 18.9     | <b>RIM REC</b> | W 15 L          |
| <b>OD (IN)</b>  | 62.2     | <b>RIM ALT</b> | W 14 L ; W 16 L |
| <b>SLR (IN)</b> | 28.0     | <b>ECE</b>     | E11-106R-005524 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|------|------|------|------|------|------|------|------|
| <b>40</b>   | 3370 | 3870 | 4440 | 5020 | 5590 | 6160 | 6730 | 7160 |
| <b>30</b>   | 3550 | 4070 | 4670 | 5280 | 5870 | 6480 | 7090 | 7530 |
| <b>25</b>   | 3690 | 4240 | 4870 | 5500 | 6130 | 6760 | 7390 | 7850 |
| <b>20</b>   | 3880 | 4450 | 5110 | 5780 | 6440 | 7100 | 7760 | 8240 |
| <b>5 LT</b> | 4520 | 5190 | 5960 | 6720 | 7500 | 8270 | 9030 | 9600 |
| <b>5 HT</b> | 3880 | 4450 | 5110 | 5780 | 6440 | 7100 | 7760 | 8240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.