

# AT 603

<b>TIRE SIZE</b>	<b>10.5/80 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	LANDWIRTSCHAFTLICHE GERÄTE / BAGGERLADER / LANDWIRTSCHAFTLICHE GERÄTE / BAGGERLADER
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	119 A8
<b>LI/SS FREE ROLLING</b>	131 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94019670	<b>RC (IN)</b>	107.4
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	35.7	<b>RIM ALT</b>	W 8; 9
<b>SLR (IN)</b>	16.6	<b>ECE</b>	E11-106R-004546

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.