

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>240/70 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	104 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94070282	<b>RC (IN)</b>	87.1
<b>SW (IN)</b>	9.6	<b>RIM REC</b>	W8
<b>OD (IN)</b>	29.2	<b>RIM ALT</b>	W 8 L; W 9
<b>SLR (IN)</b>	13.4	<b>ECE</b>	E11-106R-007531

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	940	1090	1240	1390	1560	1710	1880	1990
25	940	1090	1240	1390	1560	1710	1880	1990
20	1010	1160	1330	1500	1670	1830	2010	2130
5 LT	1260	1450	1670	1880	2090	2310	2520	2670
5 HT	1010	1160	1330	1500	1670	1830	2010	2130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.