


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94047536	<b>RC (IN)</b>	215.2
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	72.8	<b>RIM ALT</b>	DW 18 L; DD 16 L
<b>SLR (IN)</b>	32.0	<b>ECE</b>	E4-106R-000601

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	4780	5640	6420	7180	7860	8540
<b>25</b>	4780	5640	6420	7180	7860	8540
<b>20</b>	5130	6040	6870	7690	8420	9150
<b>5 LT</b>	6420	7560	8600	9620	10540	11450
<b>5 HT</b>	5130	6040	6870	7690	8420	9150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.