

LOADER SPECIAL



LOADER SPECIAL

LOADER SPECIAL (L-5) is a bias-ply tyre that keeps your loaders on the move and provides top efficiency in heavy-duty rock operations. Optimum traction and exceptional cut resistance will boost productivity.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 - 25	TL	L5	32	-	25.00/3.5	-	0	770	1930	884	5753	99,5	STD
	26.5 - 25	TL	L5	28	-	22.00/3.0	-	0	686	1815	833	5372	93,5	STD
	20.5 - 25	TL	L5	20	-	17.00/2.0	-	0	530	1570			85	STD
	29.5 - 25	TL	L5	28	-	25.00/3.5	-	0	770	1930	884	5753	99,5	STD

STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES			PERFORMANCES		
					
					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	26.5 - 25	TL	L5	32	-	22.00/3.0	-	0	686	1815	833	5372	93,5	STD
Ø33"	35/65 - 33	TL	L5	42	-	28.00/3.5	-	0	910	2105	976	6505	99,5	STD
Ø39"	40/65 - 39	TL	L5	56	-	32.00/4.0	-	0	1000	2405	0	0	108	SB
Ø45"	45/65 -45	TL	L5	58	-	36.00/4.5	-	0	1185	2785	0	0	116	SB

STD: STANDARD, SB: STEEL BELTED



TECHNOLOGIES			PERFORMANCES		
					
					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026