


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>280/85 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	122 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94072927	<b>RC (IN)</b>	117.2
<b>SW (IN)</b>	11.5	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	38.7	<b>RIM ALT</b>	W 9
<b>SLR (IN)</b>	17.6	<b>ECE</b>	E11-106R-007936

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	1360	1590	1820	2050	2280	2480	2940	3310
<b>25</b>	1360	1590	1820	2050	2280	2480	2940	3310
<b>20</b>	1450	1710	1950	2200	2450	2660	3150	3540
<b>5 LT</b>	1820	2130	2450	2760	3060	3330	3950	4430
<b>5 HT</b>	1450	1710	1950	2200	2450	2660	3150	3540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.