


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 340/85 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	139 D

## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	355	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1290	<b>RIM ALT</b>	W 11
<b>SLR (MM)</b>	571	<b>ECE</b>	E11-106R-0010342
<b>RC (MM)</b>	3833	<b>SRI</b>	625

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6
70	1215	1410	1610	1810	2010	2210
<b>FROM 65 TO 40</b>	1335	1555	1770	1990	2210	2430
30	1360	1580	1805	2025	2250	2475
20	1385	1615	1840	2070	2295	2525
10	1600	2135	2670	3200	2425	2670
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	1870	2175	2480	2785	3090	3400
10HT	1360	1580	1805	2025	2250	2475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.