


FL 630 SUPER

	710/50 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YAYICI / TANKER / RÖMORK / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	170 D



UNDEFINED US STANDARD

USA CODE	94053445	RC (IN)	166.8
SW (IN)	28.6	RIM REC	AG 24.00
OD (IN)	54.4	RIM ALT	AG 20.00
SLR (IN)	24.6	ECE	E11-106R-003009

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	3850	4450	5050	6130	7100	8180	9260	9980	11060	12010
40	4230	4890	5560	6750	7800	8990	10180	10980	12170	13230
30	5130	5930	6720	8170	9450	10890	12330	13290	14730	16000
25	5760	6670	7560	9180	10610	12230	13860	14940	16560	17990
15	6690	7740	8780	10660	12330	14220	16090	17350	19230	20900
5	7632	8820	10010	12150	14050	16190	18340	19760	21910	23810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.