

AS 504

TIRE SIZE	15.5/80 - 24
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	142 A8
LI/SS FREE ROLLING	154 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	384	RIM REC	W 12
OD (MM)	1262	RIM ALT	W 13; W 14 L
SLR (MM)	570	ECE	E11-106R-004349
RC (MM)	3875	PR	10

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.50
10 FR	5250
25 FR	4465
30 FR	4200
40 FR	3750
10 DW	3710
25 DW	3155
30 DW	2970
40 DW	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.