

# MULTIMAX MP 522

**500/70 R 24 IND**

|                     |  |
|---------------------|--|
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | KÜÇÜK YÜKLEYİCİ / TELESKOPIK<br>YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ /<br>TELESKOPIK YÜKLEYİCİ    |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 164 A8/B   |



## UNDEFINED IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 503  | <b>RIM REC</b> | DW 16 L          |
| <b>OD (MM)</b>  | 1310 | <b>RIM ALT</b> | DW 15 L; DW 18 L |
| <b>SLR (MM)</b> | 595  | <b>ECE</b>     | E4-106R-002395   |
| <b>RC (MM)</b>  | 3940 | <b>SRI</b>     | 625              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0   | 4.2   | 4.4   |
|------------|------|------|------|------|------|------|-------|-------|-------|
| 50         | 2400 | 2850 | 3250 | 3700 | 4150 | 4450 | 5000  | -     | -     |
| 40         | 2400 | 2850 | 3250 | 3700 | 4150 | 4450 | 5000  | -     | -     |
| 30         | 2570 | 3050 | 3480 | 3960 | 4445 | 4765 | 5350  | -     | -     |
| 25         | 2665 | 3165 | 3610 | 4110 | 4610 | 4940 | 5550  | -     | -     |
| 10 CYC     | 2925 | 3600 | 4240 | 4875 | 5550 | 6040 | 6825  | 7200  | 7500  |
| STATIC     | 4485 | 5520 | 6500 | 7475 | 8510 | 9260 | 10465 | 11040 | 11500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.