DATA SHEET

PRINTED ON
22-04-2026

EARTHMAX SR 315

TIRE SIZE	**26.5 R 29**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	PALA LHD
VERSIONE	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	211 A2

DIMENSIONI US STANDARD

CODICE USA	94067411	**RIM REC**	22.00/3.0
OD (IN)	73.4	**TRA CODE**	L3S
SLR (IN)	32.7	**STAR RATING**	★★
RC (IN)	221.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	76	80	83	87	91	94
5	36400	38600	39700	40800	41900	43000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..