


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 600/60 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	587	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1440	<b>RIM ALT</b>	DW 18 L
<b>SLR (MM)</b>	632	<b>ECE</b>	E11-106R-004471
<b>RC (MM)</b>	4228	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2060	2400	2735	3075	3410	3750
FROM 65 TO 40	2265	2640	3010	3380	3750	4125
30	2310	2690	3070	3445	3825	4205
20	2355	2745	3130	3515	3900	4290
10	2490	2900	3310	3715	4125	4535
*UPTO 10 CYC WITH FRONT LOADER	3170	3695	4210	4730	5250	5775
10HT	2310	2690	3070	3445	3825	4205

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.