

FLOTATION 648

| | |
|---------------------|---|
| | 600/50 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | BALYA MAKINESİ / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKİNE |
| VERSION | DUAL BEAD |
| TIRE TYPE | TL |
| | 156 A8/152 B |
| | 169 A8/165 B |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94045266 | RC (IN) | 137.8 |
| SW (IN) | 24.1 | RIM REC | AG 20.00 |
| OD (IN) | 46.1 | ECE | E11-106R-004392 |
| SLR (IN) | 20.1 | PR | 20 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 44 | 45 | 46 |
|--------------|-------|-------|-------|
| 5 FR | 17240 | 17580 | 17900 |
| 10 FR | 15510 | 15820 | 16110 |
| 20 FR | 13790 | 14060 | 14320 |
| 25 FR | 12310 | 12550 | 12790 |
| 30 FR | 11080 | 11300 | 11350 |
| 5 DW | 11880 | 12110 | 12350 |
| 10 DW | 10690 | 10900 | 11110 |
| 20 DW | 9500 | 9690 | 9880 |
| 25 DW | 8490 | 8650 | 8820 |
| 30 DW | 7640 | 7790 | 7830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.