


# AGRIMAX V- FLECTO



TIRE SIZE	VF 600/70 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D

## ABMESSUNGEN IS STANDARD

SW (MM)	603	RIM REC	DW 21 B
OD (MM)	1602	RIM ALT	DW 20 B
SLR (MM)	702	ECE	E11-106R-006162
RC (MM)	4711	SRI	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2545	2950	3360	3820	4225	4635	5095
FROM 65 TO 40	2800	3245	3695	4200	4645	5095	5600
30	2855	3305	3765	4280	4735	5195	5710
20	2910	3370	3840	4365	4830	5295	5820
10	3080	3565	4060	4620	5105	5600	6160
*UPTO 10 CYC WITH FRONT LOADER	3920	4540	5170	5880	6500	7130	7840
10 HT	2855	3305	3765	4280	4735	5195	5710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.