


# AS 504

<b>TIRE SIZE</b>	<b>15.5/80 - 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	148 A8
<b>LI/SS FREE ROLLING</b>	160 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94018987	<b>RC (IN)</b>	152.6
<b>SW (IN)</b>	15.1	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	49.7	<b>RIM ALT</b>	W 13; W 14 L
<b>SLR (IN)</b>	22.4	<b>ECE</b>	E4-106R-002816

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>51</b>
<b>5 FR</b>	13890
<b>15 FR</b>	11810
<b>20 FR</b>	11110
<b>25 FR</b>	9920
<b>5 DW</b>	9720
<b>15 DW</b>	8270
<b>20 DW</b>	7780
<b>25 DW</b>	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.