

AGRIMAX FORCE

IF 600/70 R 30

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| | 165 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 603 | RIM REC | DW 21 B; DW 21 A |
| OD (MM) | 1602 | RIM ALT | DW 20 A; DW 20 B |
| SLR (MM) | 708 | ECE | E11-106R-006495 |
| RC (MM) | 4800 | SRI | 750 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|---------------|------|------|------|------|------|------|------|------|
| 70 | 2200 | 2525 | 2900 | 3280 | 3650 | 4025 | 4400 | 4685 |
| FROM 65 TO 40 | 2420 | 2780 | 3190 | 3605 | 4015 | 4425 | 4840 | 5150 |
| 30 | 2515 | 2890 | 3315 | 3745 | 4175 | 4600 | 5030 | 5355 |
| 20 | 2610 | 3000 | 3445 | 3890 | 4335 | 4775 | 5225 | 5560 |
| 10 | 3070 | 3530 | 4050 | 4575 | 5095 | 5615 | 6145 | 6540 |
| UPTO 30 CYC | 3145 | 3610 | 4145 | 4685 | 5215 | 5750 | 6290 | 6695 |
| UPTO 15 CYC | 3750 | 4305 | 4940 | 5585 | 6220 | 6855 | 7500 | 7980 |
| UPTO 10 CYC | 4110 | 4725 | 5420 | 6125 | 6825 | 7520 | 8225 | 8755 |
| 10 HT | 2515 | 2890 | 3315 | 3745 | 4175 | 4600 | 5030 | 5355 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.