


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | 650/50 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 168 D |

DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CODICE USA | 94055654 | RC (IN) | 146.3 |
| SW (IN) | 25.4 | RIM REC | AG 20.00 |
| OD (IN) | 48.1 | ECE | E11-106R-006489 |
| SLR (IN) | 21.1 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 73 |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 3260 | 4170 | 5060 | 5740 | 6640 | 7540 | 8320 | 9120 | 10010 | 11240 |
| 40 | 3580 | 4570 | 5560 | 6300 | 7290 | 8280 | 9140 | 10010 | 10990 | 12300 |
| 30 | 4340 | 5530 | 6790 | 7630 | 8830 | 10020 | 11070 | 12110 | 13300 | 14950 |
| 25 | 4870 | 6220 | 7640 | 8580 | 9920 | 11260 | 12430 | 13610 | 14960 | 16800 |
| 20 | 5410 | 6910 | 8480 | 9510 | 11010 | 12500 | 13810 | 15110 | 16600 | 18650 |
| 15 | 5670 | 7220 | 8860 | 9950 | 11520 | 13070 | 14440 | 15810 | 17370 | 19510 |
| 5 | 6450 | 8220 | 10100 | 11340 | 13120 | 14890 | 16450 | 18000 | 19790 | 22220 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.