

FLOTATION 648

TIRE SIZE	500/60 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	153 A8/149 B
LI/SS FREE ROLLING	165 A8/161 B



DIMENSIONI US STANDARD

CODICE USA	94026364	RC (IN)	137.4
SW (IN)	19.7	RIM REC	AG 16.00
OD (IN)	46.1	RIM ALT	15.00; 17.00
SLR (IN)	20.1	ECE	E11-106R-004390

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	49	51	52
5 FR	15370	15630	15890
10 FR	13830	14060	14310
20 FR	12300	12510	12720
25 FR	10980	11170	11350
30 FR	9880	10050	10200
5 DW	10890	11080	11260
10 DW	9810	9980	10140
20 DW	8720	8860	9020
25 DW	7780	7910	8050
30 DW	7000	7120	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.