


# AW 09

<b>TIRE SIZE</b>	<b>300/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / ATTREZZI AGRICOLI / RIMORCHIO / MIETITREBBIA / ATTREZZI AGRICOLI / MIETITREBBIA
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	120 A8
<b>LI/SS FREE ROLLING</b>	132 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94037810	<b>RC (IN)</b>	99.2
<b>SW (IN)</b>	11.6	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	33.9	<b>ECE</b>	E4-106R-000375
<b>SLR (IN)</b>	14.8		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	6170
15 FR	5250
20 FR	4940
25 FR	4410
5 DW	4320
15 DW	3670
20 DW	3460
25 DW	3090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.