


# TR 678

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>800/45 - 30.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS                     |
| <b>MACHINERY</b>    | MAQUINARIA AGRÍCOLA / REMOLQUE<br>/ MAQUINARIA AGRÍCOLA /<br>AUTOCARGADORA / PALA<br>EXCAVADORA / REMOLQUE |
| <b>VERSIÓN</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 181 A2 ; 174 A8  |



## DIMENSIONES US STANDARD

|                   |          |                |                  |
|-------------------|----------|----------------|------------------|
| <b>CÓDIGO USA</b> | 94515448 | <b>RC (IN)</b> | 179.1            |
| <b>SW (IN)</b>    | 32.3     | <b>RIM REC</b> | AG 28.00         |
| <b>OD (IN)</b>    | 59.1     | <b>ECE</b>     | E11-106R-0011696 |
| <b>SLR (IN)</b>   | 26.9     | <b>PR</b>      | 20               |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 51    |
|-----------|-------|
| 25        | 14800 |
| 5         | 18200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.