


# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>495/70 R 24 MPT</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VEHÍCULO UNIVERSAL / CAMIÓN DE FERTILIZANTES / VEHÍCULO UNIVERSAL
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 G



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	499	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1304	<b>RIM ALT</b>	DW 15 L; DW 16 L; W 15 L
<b>SLR (MM)</b>	588	<b>ECE</b>	E4-54R-0029057
<b>RC (MM)</b>	3974		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.5	3.0	3.5
90	1980	2340	2840	3250	3875
65	2150	2540	3085	3530	4205
40	2280	2695	3270	3740	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.