

AGRIMAX RT 657

TIRE SIZE	420/65 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	135 D ; 138 A8



РАЗМЕРЫ US STANDARD

USA CODE	94052394	RC (IN)	150.6
SW (IN)	16.5	RIM REC	W 13
OD (IN)	49.5	RIM ALT	W 12 ; W 11
SLR (IN)	23.0	ECE	E11-106R-002974

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	2260	2600	2990	3370	3760	4130	4480	4810
30	2380	2730	3130	3540	3950	4340	4700	5050
25	2450	2810	3230	3650	4070	4480	4840	5200
20	2600	3000	3440	3880	4320	4760	5150	5530
5 LT	3030	3480	4000	4520	5040	5560	6010	6450
5 HT	2600	3000	3440	3880	4320	4760	5150	5530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.