

# AGRIMAX V-FLECTO

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | VF 620/70 R 42                                                                           |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR DE ALTA POTENCIA / TRACTOR                                                       |
| VERSIÓN      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 175 D                                                                                    |



## DIMENSIONES US STANDARD

|            |          |         |                  |
|------------|----------|---------|------------------|
| CÓDIGO USA | 94514205 | RC (IN) | 228.1            |
| SW (IN)    | 24.4     | RIM REC | DW 21 B          |
| OD (IN)    | 76.2     | RIM ALT | DW 20 B; DW 23 B |
| SLR (IN)   | 33.4     | ECE     | E11-106R-0011233 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                     | 9     | 12    | 15    | 17    | 20    | 23    | 29    |
|-------------------------------|-------|-------|-------|-------|-------|-------|-------|
| 45                            | 6920  | 8020  | 9140  | 10380 | 11490 | 12600 | 13830 |
| FROM 40 TO 25                 | 7610  | 8830  | 10040 | 11410 | 12630 | 13840 | 15210 |
| 20                            | 7760  | 9010  | 10240 | 11640 | 12870 | 14120 | 15510 |
| 12                            | 7910  | 9180  | 10450 | 11870 | 13140 | 14400 | 15820 |
| 5                             | 8370  | 9710  | 11040 | 12550 | 13890 | 15230 | 16730 |
| *UPTO 5 CYC WITH FRONT LOADER | 10650 | 12360 | 14060 | 15970 | 17680 | 19390 | 21300 |
| 5 HT                          | 7760  | 9010  | 10240 | 11640 | 12870 | 14120 | 15510 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.