


# FLOTATION 648

<b>TIRE SIZE</b>	<b>500/50 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	146 A8/142 B
<b>LI/SS FREE ROLLING</b>	158 A8/155 B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	500	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1070	<b>ECE</b>	E4-106R-001560
<b>SLR (MM)</b>	475	<b>PR</b>	16
<b>RC (MM)</b>	3200		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.60	2.80	3.00
10 FR	5475	5710	5950
20 FR	4925	5140	5355
30 FR	4380	4570	4760
40 FR	3910	4080	4250
50 FR	3520	3670	3875
10 DW	3865	4030	4200
20 DW	3480	3630	3780
30 DW	3090	3225	3360
40 DW	3760	2880	3000
50 DW	2485	2590	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.