

AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 540/65 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 149 D ; 152 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94056927 | RC (IN) | 167.4 |
| SW (IN) | 20.9 | RIM REC | W 16 L |
| OD (IN) | 55.6 | RIM ALT | W 18 L |
| SLR (IN) | 25.3 | ECE | E4-106R-000650 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 3440 | 4010 | 4520 | 5020 | 5520 | 5950 | 6590 | 7150 |
| 30 | 3620 | 4220 | 4750 | 5280 | 5800 | 6250 | 6930 | 7530 |
| 25 | 3760 | 4390 | 4940 | 5480 | 6030 | 6500 | 7210 | 7830 |
| 20 | 3970 | 4620 | 5200 | 5780 | 6350 | 6840 | 7590 | 8240 |
| 5 LT | 4620 | 5380 | 6050 | 6720 | 7400 | 7970 | 8840 | 9600 |
| 5 HT | 3970 | 4620 | 5200 | 5780 | 6350 | 6840 | 7590 | 8240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.