


AGRIMAX SPARGO

| | |
|---------------------|--|
| TIRE SIZE | VF 480/80 R 50 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 179 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|--------------------|
| USA CODE | 94057290 | RC (IN) | 245.0 |
| SW (IN) | 18.9 | RIM REC | DW 16 L |
| OD (IN) | 80.2 | RIM ALT | DW 15 L |
| SLR (IN) | 37.3 | ECE | E11-106R-004757-01 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 20 | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 47 | 49 | 52 |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 8700 | 9640 | 10560 | 11040 | 11660 | 11960 | 12270 | 12900 | 13520 | 13990 | 14610 | 15070 | 15550 |
| FROM 40 TO 25 | 9570 | 10600 | 11620 | 12130 | 12810 | 13150 | 13500 | 14180 | 14860 | 15380 | 16060 | 16570 | 17090 |
| 20 | 9760 | 10810 | 11850 | 12370 | 13070 | 13420 | 13760 | 14470 | 15160 | 15680 | 16380 | 16900 | 17430 |
| 12 | 9950 | 11020 | 12090 | 12610 | 13330 | 13680 | 14040 | 14740 | 15460 | 15990 | 16700 | 17230 | 17770 |
| 5 | 10520 | 11660 | 12780 | 13340 | 14090 | 14470 | 14840 | 15600 | 16350 | 16910 | 17660 | 18230 | 18800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.